

NIRVANA TAS

CCN: 23753924
 Rev. / ECO F 81751
 Ref.: 9903
 Page: 614
 Date: 30th April 2013
 Cancels: 27th December 2012

Point of Manufacture - Unicov, Czech Republic & Campbellsville, Kentucky USA
 ENGINEERING DATA

Model Name International	IRN22K-TAS
Model Name North America	IRN30H-TAS

GENERAL COMPRESSOR DATA					
Package Discharge Pressure	barg (psig)	7 (100)	8 (115)	8.5 (125)	10 (150)
Capacity (Ref. Intake Cond.) FAD ⁽¹⁾	m ³ /min (cfm)	3.6 (127)	3.5 (126)	3.4 (120)	3.03 (107)
Capacity at minimum speed	m ³ /min (cfm)			1.16 (41)	
Maximum Target Pressure ⁽¹²⁾	barg (psig)			10.4 (150)	
Minimum Operating Pressure ⁽¹³⁾	barg (psig)			11.0 (160)	
Minimum Target Pressure	barg (psig)			4.48 (65)	
Maximum Operating Temperature	°C (°F)			40 (104)	
Minimum Operating Temperature	°C (°F)			2 (36)	

SOUND LEVEL ⁽²⁾		
Receiver Mount / Base Mount	dB(A)	73 / 70

COOLING DATA					
Air-cooled (Ambient Temperature 40°C/104°F)					
Coolant Discharge temperature	°C (°F)	89 (193)	89 (193)	89 (193)	88 (191)
A/E Injection Temperature	°C (°F)	76 (169)	76 (169)	76 (169)	77 (170)
Aftercooler - Inlet ⁽³⁾	°C (°F)	84 (183)	84 (183)	84 (184)	83 (182)
Aftercooler - Outlet	°C (°F)	48 (116)	48 (116)	46 (115)	46 (115)
Heat Removal Oil Cooler	kW (1000 Btu/hr)	21 (70)	22 (73)	22 (73)	22 (74)
Heat Removal Oil and Aftercooler	kW (1000 Btu/hr)	24 (81)	25 (84)	25 (84)	25 (84)
Heat Removal Dryer Condenser (Max)	kW (1000 Btu/hr)	5 (15)	5 (15)	5 (9)	5 (9)
Maximum Added Static Pressure	Pa (in H ₂ O)			62 (0.25)	
Coolant Flow	lpm (gpm)	49 (13)	53 (14)	57 (15)	65 (17)
Fan Air Flow	m ³ /min (cfm)	76 (2700)	76 (2700)	76 (2700)	76 (2700)
Cooling Air CTD	°C (°F)	23 (41)	23 (41)	23 (42)	23 (42)
Aftercooler CTD, 60 Hz ⁽³⁾	°C (°F)	7 (12)	7 (12)	6 (11)	6 (11)
Aftercooler CTD, 50 Hz ⁽³⁾	°C (°F)	8 (14)	8 (14)	7 (13)	7 (13)

CONSTRUCTION FOUNDATION AND MOUNTING DATA

PIPING CONNECTIONS		
Air Discharge Base Mount	Inches NPT ⁽⁹⁾	1.50
Air Discharge from ASME Receiver	Inches NPT	1.00
Air Discharge from CE Receiver	Inches BSPT	1.00
Package Automatic Condensate Drain	Inches NPT	0.25
Coolant Drain	Drain Plug	SAE .56"-18
Diameter of Power Inlet	mm / inch	44 mm / 1.75"

COOLANT LUBRICATION DATA		
Coolant Sump Capacity	litres (US gal)	10.7 (2.8)
Total coolant fill capacity	litres (US gal)	21 (5.5)

DIMENSIONS & WEIGHT	ASME Receiver			
	Base Mounted	120 Gal Rec	240 Gal Rec	240 Gal Rec
length, width, height	mm	1630 / 766 / 1418	1930 / 822 / 2043	2339 / 822 / 2219
length, width, height	Inches	64.2 / 30.2 / 55.8	76 / 32.4 / 80	92.1 / 32.4 / 87.3
Net Weight	kg (lb.)	612 (1350)	780 (1720)	858 (1891)
Air Discharge Connection	Inches	1.5" NPT ⁽⁹⁾	1" NPT	1" NPT
GA Drawing Number		22740336	22736110	22740286
	EN 87/404 Receiver			
	Base Mounted	500 L Rec	750 L Rec	750 L Rec
length, width, height	mm	1630 / 766 / 1418	2060 / 822 / 2053	2156 / 822 / 2195
length, width, height	Inches	64.2 / 30.2 / 55.8	81.1 / 32.4 / 81	84.9 / 32.4 / 86
Net Weight	kg (lb.)	612 (1350)	804 (1772)	858 (1891)
Air Discharge Connection	Inches	1.5" NPT ⁽⁹⁾	1" BSPT	1" BSPT
GA Drawing Number		22740336	22740302	22740310

NIRVANA TAS

CCN: 23753924
 Rev. / ECO F 81751
 Ref.: 9903
 Page: 615
 Date: 30th April 2013
 Cancels: 27th December 2012

Point of Manufacture - Unicov, Czech Republic & Campbellsville, Kentucky USA
 ENGINEERING DATA

Model Name International	IRN22K-TAS
Model Name North America	IRN30H-TAS

PERFORMANCE DATA

Compressor Module

Rotor Diameter (male)	mm			107.00	
Package Discharge Pressure	barg (psig)	7 (100)	8 (115)	8.5 (125)	10 (150)
Male Rotor Shaft Speed ⁽⁸⁾	rpm	4700	4700	4520	4125
Tip Speed ⁽⁸⁾	m/sec	26.33	26.33	25.32	23.11
Tip Speed ⁽⁸⁾	ft/sec	86.37	86.37	83.06	75.80

IntelliDrive unit

Nominal Power Intellidrive Module	kW (HP)			22.5 (30)	
Applied power ⁽⁸⁾	kW (HP)			24.8 (33.0)	
Rated Power - Fan	kW (HP)			1.3 (1.75)	
Applied Power - Full Package ⁽⁸⁾	kW (HP)			26.1 (34.75)	
IntelliDrive Efficiency ⁽⁵⁾	Percent			97%	
Main Motor Efficiency	Percent			93.5%	
Fan motor efficiency	Percent			85%	
Applied Power - Dryer Compressor	kW			1.5	
Input kW at maximum target pressure	kW	29.8	31.2	31.0	30.1
Specific Power ⁽⁴⁾	kW/100cfm	23.3	24.6	25.8	28.1
	kW/m ³ /min	8.3	8.7	9.1	9.9

ELECTRICAL DATA

		208V	220V	230V	380V	400V	460V
Motor / Drive Protection		IP55 / NEMA 12 / TEAO			IP55 / NEMA 12 / TEAO		
Drive Motor Frame		160L			160L		
Current - Intellidrive ⁽⁸⁾	Amps	85.4	79.5	76.3	48.2	44.1	38.5
Current - Cooling fan	Amps	5.2	5.2	4.9	2.8	2.7	2.4
Package Current @ Max Target Press	Amps	95.8	89.9	86.1	53.7	49.5	43.2
Intellidrive inrush current	Amps	85.4	79.5	76.3	48.2	44.1	38.5
Package inrush current	Amps	129.6	123.7	118.0	71.6	67.1	58.5
Package Power Factor ⁽⁸⁾		0.90	0.90	0.90	0.90	0.90	0.90
Electrical Installation							
Recommended Supply Cable Size ⁽¹⁰⁾	mm ² /Cu	32	32	32	16	16	16
Minimum Supply Cable Size (NEC) ⁽¹⁰⁾ ⁽⁶⁾	AWG	2	2	2	6	6	6
Maximum Fuse Rating ⁽⁷⁾ ⁽¹⁰⁾	Amps	175	175	175	90	90	90

Refrigerated Dryer Data

Pressure Dew Point ISO Class ⁽¹¹⁾	°C (°F)	ISO Class 5	lower than 5°C (41°F)
Refrigerant weight of R-134a	Grams (Oz)	610 (22)	

Filter Data

	CCN	Particulate		Liquid	
		ISO Class	Filtration	ISO Class	Filtration
Primary filter detail - at 21°C (70°F)	85567329	3	1 micron	3	0.5 mg/m ³ (0.5 ppm)
Final filter detail - at 21°C (70°F)	85567337	2	0.01 micron	1	0,01 mg/m ³ (0.01 ppm)

Pressure Drop Data

	barG / (psig)	barG	psig	barG	psig	barG	psig
Dryer Pressure Drop		8.0	115	8.6	125	10.3	150
Primary Pressure Drop	barG / (psig)	0.14	2	0.13	1.9	0.10	1.5
Dryer filter wet pressure drop	barG / (psig)	0.14	2	0.12	1.8	0.10	1.5
Final filter wet pressure drop	barG / (psig)	0.19	2.8	0.19	2.7	0.16	2.3
Total Pressure Drop ⁽¹⁴⁾ ISO Class 2.5.1 Air	barG / (psig)	0.47	6.8	0.44	6.4	0.37	5.3

Notes :

- (1) FAD (Free Air Delivery at actual inlet conditions) is full package performance including all losses. Tested in accordance with ISO 1217 : 1996 Annex C.
- (2) Measured in free field conditions per ISO 2151 using Hemispherical Method, with + 3 dB(A) tolerance.
- (3) 40% Relative Humidity Inlet Air and maximum speed (For alternate conditions refer to SSR toolbox or contact IR)
- (4) Specific power guaranteed in accordance with ISO 1217 : 1996 Annex C
- (5) "Intellidrive" includes variable frequency drive electronics
- (6) This is a minimum requirement based on 90°C wire - It may be necessary to use larger cables to comply with local regulations or if the voltage drop exceeds 5% of the nominal voltage.
- (7) Must be Fast acting Class-J, T or semiconductor type, Current limiting, Interrupt rating-200,000 Amps RMS SYM
- (8) Measured at rated capacity and maximum target pressure
- (9) Regional Installation kit will provide flexible connection to NPT or BSPT
- (10) Always apply local electrical codes for sizing cables and fusing.
- (11) Dew point measured in accordance with Iso 8573-1:2001 with inlet air to package of 25 °C (77°F) and RH of 60%
- (12) Target discharge pressure, sensed by pressure transducer located at package discharge
- (13) Maximum pressure at package discharge, value at which compressor will stop when unit operating at maximum target pressure
- (14) Total Air System package including compressor, integral dryer with pre and final compressed air filters