



ENGINEERING DATA SHEET

R75i Total Air System (TAS) 60Hz

CCN: 23769706
Rev.: H
ECN: 83739
Sheet: 1 of 2
Date: 16-Jun-2015

Model Name		R75I-X103-TAS	R75I-X118-TAS	R75I-X138-TAS	R75I-X193-TAS
GENERAL PERFORMANCE DATA					
Maximum Operating Pressure (2)	barg (psig)	7 (103)	8 (118)	9.5 (138)	13.5 (193)
Rated Discharge Pressure	barg (psig)	7 (100)	8 (115)	9.5 (135)	13.5 (190)
Minimum Operating Pressure	barg (psig)	4.5 (65)	4.5 (65)	4.5 (65)	4.5 (65)
Capacity FAD (1)	m ³ /min (CFM)	13.54 (478)	12.88 (455)	11.84 (418)	9.40 (332)
Maximum Operating Ambient Temperature	°C (°F)		46 (115)		
Minimum Operating Ambient Temperature	°C (°F)		2 (35)		
Maximum System Temperature Setting	°C (°F)		109 (228)		
Nominal Power - Main Motor	kW (HP)		75 (100)		
Main Motor Efficiency (3)	Percent		95.4%		
Pkg Input Power w/Fan and Dryer- Air Cooled (4)	kW	94.2	95.6	95.8	95.4
Pkg Input Power w/Fan and Dryer - Water Cooled (4)	kW	91.8	93.2	93.4	93.0
Specific Power - Air Cooled (4)(5)	kW/m ³ /min (kW/100cfm)	6.96 (19.71)	7.42 (21.01)	8.09 (22.92)	10.15 (28.73)
Specific Power - Water Cooled (4)(5)	kW/m ³ /min (kW/100cfm)	6.78 (19.2)	7.23 (20.48)	7.89 (22.34)	9.89 (28.)
SOUND LEVEL (6)					
Standard Package - Air Cooled	dB(A)			69	
Standard Package - Water Cooled	dB(A)			69	
COOLING DATA (@ Maximum Ambient Temperature & Maximum Discharge Pressure)					
Heat Removal Oil Cooler	kW (1000 Btu/hr)	69 (237)	71 (242)	72 (246)	73 (249)
Heat Removal Oil and Aftercooler	kW (1000 Btu/hr)	89 (302)	90 (307)	91 (309)	90 (307)
Additional Static Pressure (15)	Pa (in H ₂ O)		60 (.25) - 250 (1.0)		
Air-cooled					
Fan Air Flow	m ³ /min (CFM)		176 (6200)		
Fan Motor Nominal Power	kW		2.2		
Cooling Air Temperature Rise	°C (°F)	34 (62)	35 (63)	35 (63)	35 (63)
Aftercooler CTD(7)	°C (°F)	8 (15)	8 (15)	8 (15)	8 (15)
Water-cooled - Standard Duty					
Fan Air Flow	m ³ /min (CFM)		76 (2700)		
Fan Motor Nominal Power	kW		0.4		
Aftercooler CTD (7)(8)	°C (°F)	8 (15)	8 (15)	8 (15)	8 (15)
Cooling Water Flow					
@ 10°C (50°F)	l/min (gal/min)	74 (20)	75 (20)	76 (20)	75 (20)
@ 20°C (68°F)	l/min (gal/min)	75 (20)	76 (20)	77 (20)	76 (20)
@ 30°C (86°F)	l/min (gal/min)	77 (20)	78 (21)	79 (21)	78 (21)
@ 40°C (104°F)	l/min (gal/min)	79 (21)	81 (22)	81 (22)	80 (21)
@ 46°C (115°F)	l/min (gal/min)	82 (22)	84 (22)	84 (22)	83 (22)
Cooling Water Temperature Rise @ 30°C	°C (°F)	15 (28)	15 (28)	15 (28)	15 (28)
Cooling Water Pressure Drop	bar (psi)		Less than .88 bar (13psi)		
Cooling Air Temperature Rise @ 30°C	°C (°F)	4 (8)	5 (8)	5 (8)	5 (8)
Water-cooled - Harsh Duty					
Fan Air Flow	m ³ /min (CFM)		76 (2700)		
Fan Motor Nominal Power	kW		0.4		
Aftercooler CTD (8)	°C (°F)	8 (15)	8 (15)	8 (15)	8 (15)
Cooling Water Flow					
@ 10°C (50°F)	l/min (gal/min)	128 (34)	130 (35)	131 (35)	131 (35)
@ 20°C (68°F)	l/min (gal/min)	130 (35)	132 (35)	134 (36)	133 (35)
@ 30°C (86°F)	l/min (gal/min)	133 (35)	136 (36)	137 (36)	136 (36)
@ 40°C (104°F)	l/min (gal/min)	139 (37)	142 (38)	143 (38)	141 (38)
@ 46°C (115°F)	l/min (gal/min)	144 (38)	147 (39)	148 (39)	146 (39)
Cooling Water Temperature Rise @ 30°C	°C (°F)	10 (18)	10 (18)	10 (19)	10 (19)
Cooling Water Pressure Drop	bar (psi)		Less than .88 bar (13psi)		
Cooling Air Temperature Rise	°C (°F)	5 (8)	5 (9)	5 (9)	5 (9)
Air End Data					
Male Rotor Speed	rpm	3329	3194	2945	2420
Tip Speed Rotor	m/sec	31.11	29.85	27.52	23.60
Full Load Shaft Power	kW	82.5	83.8	84.0	83.6

CONSTRUCTION, FOUNDATION, AND MOUNTING DATA
PIPING CONNECTIONS

Air Discharge	Inches BSPT/NPT (9)	2.00
Package Automatic Condensate Drain	Inches BSPT/NPT (9)	0.38
Coolant Drain Plug	Inches BSPT/NPT (9)	0.75
Diameter of Power Inlet	mm / inch	Upto 4"(removable plate)
Water Inlet and Outlet Connections	Inches BSPT/NPT (9)	1.50

COOLANT LUBRICATION DATA

Total Coolant Capacity - Air Cooled	litres (US gal)	49 (13)
Total Coolant Capacity - Water Cooled - Std	litres (US gal)	31 (8)
Total Coolant Capacity - Water Cooled - Harsh	litres (US gal)	TBD

DIMENSIONS & WEIGHT

		Base Mounted
Length / Width / Height	mm (inches)	2432(95.8) / 1265(49.8) / 2032 (80)
Net Weight - Air Cooled	kg (lb.)	1868 (4118)
Net Weight - Water Cooled	kg (lb.)	1761 (3883)
GA Drawing Number - Air Cooled		23701352
GA Drawing Number - Water Cooled		23701345

ELECTRICAL DATA ⁽¹⁴⁾

		230V. 3Φ	380V. 3Φ	440V. 3Φ	460V. 3Φ	575V. 3Φ
Motor Enclosure Protection		IP 55				
Full Load Package Current - Air Cooled (10)	Amps	296	186	154	148	118
Full Load Package Current - Water Cooled (10)	Amps	288	182	150	144	115
Package Locked Rotor Current	Amps	1534	928	802	767	614
Package Power Factor		0.88	0.88	0.88	0.88	0.88

Electrical Installation

		230V. 3Φ	380V. 3Φ	440V. 3Φ	460V. 3Φ	575V. 3Φ
Recommended Supply Cable Size (11)	mm ² /Cu (AWG or kcmi)	240(500)	95(4/0)	95(3/0)	95(3/0)	50(1/0)
Maximum Recommended Fuse Rating ⁽¹¹⁾⁽¹²⁾	Amps	400	250	250	200	150

Refrigerated Dryer Data

		ISO Class
Pressure Dew Point ISO Class(16)	°C (°F)	4
Refrigerant Weight of R-404a	Grams(oz)	1800(63.5)

Filter Data

	Particulate		Liquid	
	ISO Class	Filtration	ISO Class	Filtration
Filter Detail - at 21°C (70°F)	2	0.01 micron	1	0.01 mg/m ³ (0.1 ppm)

Notes :

- (1) FAD (Free Air Delivery) is full package performance including all losses. Tested per ISO 1217 : 2009 Annex C
- (2) Maximum pressure at package discharge, value at which compressor will stop when unit operating at maximum target pressure
- (3) IE3 efficiency motor
- (4) Measured at rated capacity and rated pressure
- (5) Specific power guaranteed in accordance with ISO 1217 : 2009 Annex C
- (6) Measured in free field conditions per ISO 2151 using Hemispherical Method; ducted inlet and outlet, with + 3 dB(A) tolerance.
- (7) 40% Relative Humidity Inlet Air and maximum speed (For alternate conditions contact Ingersoll Rand)
- (8) Ambient temperature equivalent to cooling water inlet temperature
- (9) BSPT or NPT, depending on regional standard
- (10) Maximum current includes 10% additional current due to fouled filters and elements
- (11) 90°C copper cables. Always apply local electrical codes for sizing cables and fusing.
- (12) Time delay fuse recommended. Apply local electrical codes for fuse sizing
- (13) Coolant volumes listed are approximate. See operator manual for coolant fill procedure.
- (14) Voltage tolerance: (380) ±6% ; (440,460, 575) ±10%
- (15) See detailed scope document 23883374
- (16) TAS units deliver ISO Class 1-4-2 quality air measured at steady state conditions in accordance with ISO 8573-1:2010, with inlet air to package of 25°C (77°F) and RH of 60%.

Product Improvement is a continuing goal at Ingersoll Rand. Design and specifications are subject to change without notice or obligation.