
DETAILED SCOPE

INGERSOLL RAND single stage and two stage contact cooled, rotary screw packaged air compressor.

GENERAL PACKAGE DESCRIPTION:

The fully packaged contact cooled, rotary screw air compressor is designed for total convenience, it is easy to install, simple to operate and will deliver rated compressed air with reliable efficiency. The enclosure is designed to manage the environment of the internal components and the cooling ventilation system, at the same time as significantly reducing the sound level emitted from the machine into the installation environment. The complete package is designed to be located on an adequate flat floor without any special foundations and will operate without imparting significant vibrations to the installation.

INLET AIR FILTER:

Inlet air filtration is accomplished by a large dry type air cleaner. Minimum efficiency at 3 microns is 99.0% (ISO 12103-1 A2 fine dust at a velocity of 15 cm/s). This is more than suitable for the vast majority of applications: however, where high dust and dirt contamination is present, optional enhanced filtration systems are available.

COMPRESSION MODULE / AIR END:

Since the air-end is the fundamental component in any rotary screw compressor package, reliability, performance and efficiency are determined for the most part by the design, manufacturing tolerances and assembly of the air-end itself. All other elements in the compressor system are essentially support and monitoring devices included to ensure dependable service and performance.

The rotors are manufactured from AISI-1045 steel or EN 10083-2 C45+N steel. The asymmetrical helical profile is developed through a unique two step machining process. The first step in the machining process develops the basic wrap angle profile and is a rough cut. The second and final step is a finish grinding process which ensures a hard, true rotor surface. The optimized machining process produces extremely precise rotors which consistently deliver high performance. The rotor housings are made of close grain high quality cast iron. After machining the housing is dimensionally checked to ensure accuracy.

DETAILED SCOPE

The bearing configuration at discharge end consists of a cylindrical roller bearing, angular contact bearings, and a deep groove ball bearing. The cylindrical roller bearing handles the radial loads while the angular contact bearings support the thrust loads.

Cylindrical roller bearings are used to carry the radial loads on the inlet end of the rotors.

All bearings whether thrust or radial, use premium cost vacuum degassed bearings, which provide truer, harder running surfaces for both inner and outer bearing races. This bearing configuration allows for extremely tight control of clearances during operation and reduced power losses for improved efficiency.

To ensure these bearings receive the proper amount of lubricant, specifically located oil passageways deliver a controlled amount of oil to the bearings and ring seals separate the bearings from the compression chamber. This ensures the bearings always receive the correct amount of lubricant which maximizes life and optimizes efficiency.

The two stage air-ends have the compression divided into 2 stages for added reliability and efficiency.

DRIVE MOTOR (Fixed Speed):

The main drive motor is exactly matched to the requirements of the compressor. Torque and shaft load requirements of the compressor were matched to design criteria that enable the motor to develop peak efficiency and power factor at full load of the compressor package. Standard units are supplied with IP55 motors, meeting or exceeding IE3 (IEC60034-30) and NEMA Premium[®] efficiency rating requirements for totally enclosed fan cooled motors.

- **Frame** - The cast iron IEC frame motor is foot and flange mounted. The frame design is specified to provide maximum strength and rigidity for bearing support, uniform stator/rotor gap and permanent alignment of all mating parts.
- **Electrical Design** - Speed, torque and operating characteristics have been designed to match the load of the compressor. Motor efficiency and power factor have been optimized. Standard motors are available in 50Hz (400V) and 60Hz (380, 440, 460 and 575V). 400V 50Hz motors are suitable for 380-415V rated supplies

DETAILED SCOPE

- **Bearings** - Vacuum degassed bearings provide dependable and reliable service. The motor shaft has the largest possible standard diameter. This means that larger bearings are fitted. The average applied life is approximately five times greater with these oversized bearings than standard bearings. Both bearings are grease lubricated with bearing housings having inlet and relief fittings to simplify the lubrication procedures.
- **Insulation** - The Ingersoll Rand dedicated motor has a major benefit in that the maximum temperature rise the motor actually experiences is much lower than the temperature rise permitted by the design of the motor. The motor has class F insulation as standard, which means it is rated at a continuous duty for a temperature rise up to 109°C (228°F). Design limits the actual temperature rise to not exceed 89°C (192°F) in a 46°C (115°F) ambient. This is significant, since the motor life expectancy is doubled with every 10°C reduction in temperature rise. This conservative application leads to better reliability, increased life, and a much more forgiving motor under adverse conditions.
All windings and leads are copper with triple coats of insulating varnish to add extra margins of protection to the motor.
- **Temperature Monitoring** - RTDs monitor the temperature of the windings and bearings, and ensure that the motor and hence the package does not run outside of the environmental and load conditions.
- **Space Heaters** - The motors have built-in space heaters as standard for low ambient applications.
- **DRIVE MOTOR (Variable Speed Induction):**

Machines with integral variable frequency drive utilize motors specifically designed for the purpose. In addition to all the features for fixed speed induction machines, the windings have a minimum 1600V winding withstand (1800V for 575V). Additional motor protection is included as standard with thermally protected stator windings (one device per phase). Motor speed is controlled using pulse width modulation (PWM) vector type motor control.

INTEGRAL DRIVE ASSEMBLY:

In order to maximize the inherent efficiency advantage of the Ingersoll Rand motor and air-end it was necessary to develop a means of efficiently and reliably transmitting

DETAILED SCOPE

power from the motor to the compressor. The Ingersoll Rand integral gear drive system was engineered to operate without losses or slip and without mechanical complexity of alignment compensating couplings. The reliable and rugged design has been refined and proven over more than a quarter century of use.

Conservatively chosen speed optimizing gears are mounted on the shafts of the air-end and motor. These smooth running helical gears dictate that the air-ends always rotate at the selected speed which provides consistent capacity and efficiency. The gear housing is completely sealed against atmospheric contaminants to ensure lifetime trouble-free power transmission. A self-centering PTFE impregnated motor shaft seal provides a positive system against leakage to the motor winding.

VIBRATION MOUNTS:

The air-end / motor module is mounted to the sub-base on anti-vibration pads.

LUBRICATION SYSTEM:

Elements of the lubrication system include;

- **Coolant Filtration** - The full capacity replaceable coolant filter element is 99.5% efficient at 10 micron ($\beta_{10} \geq 200$ – ISO 4572). Filter condition is monitored by the controller which provides a warning when filter differential reaches 1.8 bar (25 psi). The system contains an internal pressure relief that bypasses at 2.5 bar (36 psi) in the event that the change warning is not acknowledged.
- **Coolant/Lubricant Temperature Control** - The thermostatic control valve with four ports, (1) for the coolant from the pressurized receiver/separator, (2) for the coolant from the valve to the cooler, (3) for the coolant from the cooler, and (4) for the coolant to the coolant filter, is mounted in the piping system. The temperature sensitive element controls the quantity of coolant from each source, cooled and un-cooled as necessary to provide the proper injection temperature, ensuring fast warm-up and avoiding potentially harmful condensation.
- **Coolant Injection** - The coolant is injected through a single large port on the female rotor inlet side. This ensures the best possible pre-sealing of the rotor, plus an optimum mix of coolant with inlet air. Coolant flow is maintained by the differential pressure between the separator tank and the air-end inlet.

DETAILED SCOPE

COOLANT/AIR SEPARATION:

After compression and discharge from the air-end, the coolant laden air travels to the receiver/separator. Entering through a tangential inlet, the air coolant mixture is directed in a circular motion around the inside of the tank. The vortex or the circular motion separates a major portion of the coolant from the air through centrifugal force. The air is then directed through baffles, which further reduces the coolant content. The vortex action and impingement on baffles results in a pre-cleaning of the compressed air prior to entering the separator element.

Separator element is two-stage molded fiberglass structurally reinforced coalescing separator. There is a scavenge line which picks up coolant which has coalesced on the inside of the separator element and feeds it back to the air-end inlet. The carryover after the separator element is less than 3 ppm. Due to the conservative sizing of the separator element there is a minimal 3 psi (0.2 bar) pressure drop. This reduces the required power to move the air through the compressor system.

The separator tank is mounted vertically in the compressor with the air-end discharge entering near the bottom. The separator vessel is protected by pressure relief safety valve mounted on the side of the tank. There is a coolant drain valve at the bottom of the tank and a coolant filler point which is located so that it is not possible to overfill the compressor with coolant. There is also a coolant sight level glass on the side of the tank. The air discharge from the separator is regulated by a minimum pressure check valve which ensures that, when the unit is unloaded, sufficient pressure is maintained in the tank to propel the coolant through the system.

Pressure reducing blow down valves allow the pressure in the separator tank to be reduced when the machine is unloaded, when this valve opens, the internal pressure falls to approximately 20 psig (1.4 barg) which minimizes the unloaded power requirement.

COOLANT:

Ingersoll Rand compressors are factory filled with Ultra Extended Life (EL) advanced synthetic lubricant which performs up to twice as long as other rotary lubricants, minimizing downtime and lowering lifecycle costs. Ultra EL is expected to last 16,000 hours in the typical applications, offers superior wear protection, better corrosion protection and improved performance in the presence of air and water

DETAILED SCOPE

COOLERS:

In standard air cooled units the discharge air is cooled to as low as within 8.3°C (15°F) of the ambient temperature, basis 38°C (100°F) and 40% RH. In air-cooled units cooling air which is drawn into the enclosure passes over the main motor and air-end and is then forced out through the after-cooler and coolant cooler. The coolers are of an aluminum finned tube construction and are designed to operate continuously, fully loaded in ambient air up to 46°C (115°F).

Air-cooled Variable Speed Drive (VSD) compressors utilize a "COOLANT CONDITIONER" system to ensure that proper coolant temperature is maintained. The system is a combination of an inverter controlled cooling blower motor, and coolant system thermostatic control valve. The controller uses data from the cooling system, to identify an optimal target temperature, then directs the blower motor inverter to work in conjunction with the thermostatic control valve to maintain it. This sophisticated system provides:

- a) Enhanced protection against damaging moisture accumulating in the coolant system
- b) Optimal after-cooling throughout the entire performance range of the compressor
- c) Significant sound reduction at partial loading
- d) Additional energy savings by reducing fan motor power under most conditions

Water-cooled machines have an aftercooler CTD of 8°C (15°F) and can be adjusted depending on the available cooling water temperature and flow. Cooling is achieved with parallel water flow into the two coolers and is designed for cooling water inlet temperatures up to 46°C (115°F). The heat exchangers are constructed with robust shell and tube design and are horizontally mounted for ease of service. Optional copper nickel tubing coolers are available for harsh and sea water applications.

DETAILED SCOPE

FAN MOTORS:

In air-cooled machines, the TEFC motor and the low noise, high pressure, centrifugal blower is mounted behind the coolers. This forces a cooling air flow through the cooler prior to exiting the enclosure. A residual pressure is increased due to ducting losses, the maximum ambient temperature decreases accordingly.

Additional Static Pressure (inches H₂O/Pa)	LAT (°F)	LAT (°C)
0.25 / 65	111	44
0.50 / 125	109	43
0.75 / 185	109	43
1.00 / 250	108	42

COMPRESSOR/ CAPACITY CONTROLS (Fixed Speed):

As standard, units are provided with on line/off line control. This control strategy allows the compressor to operate at 2 points on the capacity curve. The first is 100% full-flow and the second is zero flow. On line/off line control is a power savings mode of operation where the unloaded operation provides for immediate compressor system blow-down to minimize power requirements. The compressor will automatically reload to 100% capacity when the system pressure falls to a predetermined pressure.

Automatic stop/start is standard that allows the compressor to run unloaded for a predetermined time, and if there is no demand within that period, the unit shuts down to standby, consuming zero energy and will automatically restart and load if the pressure falls to a preset level.

The time at which the compressor is operating most inefficiently is when the compressor is running unloaded. The controller will monitor the compressor's operating cycle and reduce the off load running time to a minimum.

Upper range modulation control is an option on these compressors. Refer to the option section for details.

DETAILED SCOPE

COMPRESSOR/ CAPACITY CONTROLS (Variable speed):

The compressor is controlled by one of the advanced Xe Series machine controllers. These highly automated controls allow for a high turndown range while maintaining a system efficiency of 92% or greater. The compressor will turn itself off at minimum speed (subject to minimum run times) and remain off until system pressure decays below operator set target pressure.

STARTER (Fixed Speed):

The standard compressor has an integrally mounted IP55 (NEMA 4 – North America) starter box with a hinged door panel. It contains starter contactors, control transformer and all the components of the control circuit. The star-delta starter is used to reduce the current inrush on starting. The control relays operate at 110V AC and the control circuit is protected by miniature circuit breakers or fuses. All electrical equipment is designed to conform to the applicable local electrical codes. An optional electronic soft starter is available. US models have a minimum 10kA SCCR.

INVERTER (Variable speed):

A standard feature of the variable speed drive compressors is the integral inverter, which has been engineered to perform optimally with the compressors drive motor. The inverter has a minimum efficiency of 96% throughout its operating range. Integral to the drive module is the control voltage circuit, which provides control power for all control circuits. The inverter also provides phase loss and phase reversal protection. Integral line reactor is also a standard feature.

PHASE MONITOR (standard for Fixed Speed 2S only):

Phase monitor that detects phase loss, phase reversal, low voltage (brown out) and phase imbalance

Package Pre-filter:

Package pre-filter is standard to all packages. It pre-cleans the air going into the air-end and the package. In the process keeps the electrical and cooling subsystems, and the inside of the package clean.

DETAILED SCOPE

Moisture Separator and Condensate Drain:

Internally mounted moisture separator is standard to all packages, with factory configurable Timed Solenoid drain or Electronic No Loss Drain (ENLD). The 1S Fixed Speed machines have the Timed Solenoid as standard and ENLD as option. All VSD machines and 2S Fixed speed machines will have the ENLD as standard.

XE SERIES CONTROLLER:

The compressor is monitored, controlled and protected by an intuitive Xe Series controller. The controller continuously monitors the status of the compressor and takes immediate action if an abnormal operating condition occurs. The controller also has several features which make operating the compressor easier and more efficient.

	Xe-145M
Display	5.7" VGA Color
Total I/O's	44
Ethernet Port	Yes
USB Port	Yes
Data Collection (SD Card)	30 days
Language	31 Languages text

LANGUAGES:

Bulgarian	Chinese	Croatian	Czech
Danish	Dutch	English	Estonian
Finnish	French	German	Greek
Hungarian	Indonesian	Italian	Japanese
Korean	Latvian	Lithuanian	Maltese
Norwegian	Polish	Portuguese	Romanian
Russian	Slovak	Slovenian	Spanish
Swedish	Thai	Turkish	

DETAILED SCOPE

	Xe-145M
Start/Stop Control	X
Manual Load/Unload	X
Auto-Restart	X
Modulation (FS)	X
Mod/ACS (FS)	X
Lead/Lag(FS)	X
Power Out Restart	OPT
Progressive Adaptive Control (PAC)	X
Remote Pressure	X
Remote Start/Stop	X
Remote Load/Unload	X
Monitoring	
Coolant filter monitoring	X
Inlet filter monitoring	X
Independent main motor and fan motor overload	X
Independent warning and trip fault outputs	X

DETAILED SCOPE

	Xe-145M
Sequencing (Xe units only)	
# compressors	4
Use local compressor pressure transducer	X
Programmable on Elapsed Time	X
FIFO (First in - Last out)	X
Controller Failure, Revert to local	X
Prioritized Compressor Selection	X
Interface	
Energy savings calculator	VS Only
Graphing and trending	X
Standard web pages	X
Remote control via web pages	X
Automated reporting	X
Web-based graphing/trending	X
Email notification	X

DETAILED SCOPE

HARDWARE:

Display Communication Unit (DCU)

- LCD graphic display window w LED back light
- 3 - LED Status Indicators (Green – OK, Red – Fault, Blue – Automatic Start)
- Tabbed folders for ease of navigation
- Multiple screens of compressor information and setup data
- Status Bar with compressor state and 4 Status Icons
- Left/Right/Up/Down/Enter push buttons
- Acknowledge/Reset push buttons
- Start/Stop push buttons
- Load/Unload push buttons

CONTROLLER EVENT LOG:

The Event Log is a comprehensive listing of the most recent occurrences with name, time, date and value. The Event Log contains details on the last 250 "events" in order of occurrence.

Logged events

- Start inhibit
- Warnings
- Trips
- Command key press (local and remote)
- E-Stop pressed
- Module control power up and down
- Analog input failed
- User interacted start and stop
- Compressor Started

DETAILED SCOPE

COMMUNICATIONS:

The controller can be accessed through the following standard access points.

- Serial - RS485
 - Modbus RTU
 - System Controller / Integral sequencing
- Ethernet
 - Modbus TCP
 - Field Service Tool Remote access
- USB (Service Port)
 - PC direct connection for Field Service Tool.
- Hard Wired Communication
 - Trouble Indication Contacts (Warning and Trip, Running Unloaded Contact)

SEQUENCE CONTROL:

The controller is suitable for use with Ingersoll Rand approved energy management controllers. In addition, the controller on the fixed speed and VSD units can automatically sequence up to four compressors fitted with the Xe-70M, Xe-90M or Xe-145M controllers via the RS485 serial communication interface, sharing running hours, operating on a common pressure range and changing running order in accordance with a pre-programmed schedule.

When controlling an air system with an Ingersoll Rand Air System Controller, which sequencers multiple compressors and accessories, connect directly to the compressors via the RS485 serial communication interface.

DETAILED SCOPE

OPTIONS

POWER OUTAGE RESTART (PORO):

For the “real time clock” timed operation function which is available within the controller, or for customers who anticipate interruptions in their incoming power supplied to their compressors, but need to maintain their supply of compressed air, the Power Outage Restart Option allows the compressor to restart automatically within an adjustable time period after incoming power is restored following power interruption.

The option consists of an audible warning device and full fitting instructions. The siren, which sounds when power is restored to the compressor, warning people in the vicinity that the unit is about to start. This is mounted into the instrument panel.

HIGH DUST FILTER (Fixed Speed Only):

This is a heavy duty and high capacity filter, enclosed in a plastic shroud, for use in dirty, dusty environments. The filter has two stages of separation; a centrifugal primary stage is employed to mechanically separate larger dust particles which are ejected, followed by a high capacity dry type filter element. Minimum efficiency at 3 microns is 99.0% (ISO 12103-1 A2 fine dust at a velocity of 15 cm/s).

CONTAINMENT BASE:

This variation of the standard rugged base frame has a welded and sealed tray to provide a full containment of lubricant in the event of spillage during maintenance and can contain the full sump capacity of lubricant.

UPPER RANGE MODULATION CONTROL (Fixed Speed Only):

Modulating inlet control automatically matches air capacity to demand. This control method reduces the delivered air volume by causing a pressure reduction in the intake port. When modulation is fitted and selected, partial closure of the intake valve in direct relation to fall and rise of pressure will cause variable air volume delivery. Modulation is available as an option. Modulation control is particularly useful where air demands vary between 60 & 100% (which is most common situation) and where there is some reasonable amount of system storage capacity.

DETAILED SCOPE

Modulation avoids the frequent cycling which is sometimes associated with on-line/off-line control when insufficient system capacity is available, in which case modulation reduces the thrust loads on bearings and cycling of solenoid valves.

LOW AMBIENT FREEZE PROTECTION (Fixed Speed Only):

Starting a compressor with viscous coolant, condensation within the electrical components or frozen condensate drainage systems can all result in damage. To protect against such an event the controller will warn if freezing conditions occur at start-up, and if heaters are fitted will execute a warm-up cycle prior to loading. For units to be installed in conditions with temperatures down to -10°C (14°F) (-23°C, -10°F for North America), Ingersoll Rand offer a combination of heating elements in the starter panel, trace heating and motor heaters or fan assisted space heaters to prevent moisture or freezing of condensate when the unit is shut down. The heaters can be wired directly to a suitable customers' supply voltage or through the starter so they can switch on when the units shut down. Through a VFD on the blower, the controller maintains proper compressor temperatures even in the cold environment. NOTE: Outdoor Modification is a separate option and can be ordered in conjunction with freeze protection.

OUTDOOR INSTALLATION RAIN INGRESS PROTECTION (Fixed Speed Only):

Intended for operation between temperatures of 35°F (2°C) through 115°F (46°C) in installations which may be exposed to rain ingress this option will ensure that sensitive electrical areas are ingress protected and any water penetration into general machine is channeled out of the enclosure appropriately.

ELECTRONIC SOFT STARTER (Fixed Speed Only):

The optional soft start facilitates reducing starting current to the lowest value achievable, compatible with positive starting of the drive motor. This system is offered to overcome issues where local equipment is sensitive to, or expected to be effected by disturbances in power supplies caused by relatively high starting currents and transient spikes caused by traditional contactor switching motor starters. All soft starters are integrally mounted inside compressor starter box.

PHASE MONITOR (option for Fixed Speed 1S; standard for Fixed Speed 2S):

An optional phase monitor can be specified that detects phase loss, phase reversal, low voltage (brown out) and phase imbalance.

DETAILED SCOPE

COOLANTS:

Optional Ingersoll Rand Premium Coolant or Ultra FG (H-1F food grade) may be used with this compressor.

Ingersoll Rand Premium Coolant; a polyalkylene glycol (PAG) advanced full synthetic lubricant, providing better cooling characteristics, reduced wear through improved lubrication, and has a longer operating life than other synthetic lubricants.

Ultra FG is an H-1F and NSF certified food grade lubricant designed specifically to help customers in the food and beverage industries meet their production quality standards. Ultra FG offers longer life compared to commercial food grade compressor lubricants (6000 hours +). Ultra FG also has outstanding anti-wear protection and exhibits resistance to formulation of foam, sludge, varnish, and corrosive acids.

MEDIUM VOLTAGE Motors:

Voltage options for 2300V, 3300V, 4000V, 6000V and 10kV are available for the fixed speed units. The electrical design and robustness are equivalent to the standard voltage motors. They have the same cast iron frame, IP55 protection, Class F insulation and temperature monitoring like the standard voltage motors.

High Dust Package Pre-filter:

High dust Package pre-filter option is available for dirtier environments to pre-clean the air going into the air-end and the package.

Remote Sensing:

Remote sensing option enables the customer to load/unload the compressor from a pressure sensor located at customer desired point, instead of the compressor package discharge.

High Ambient Option:

The high ambient option allows the compressor to operate at ambient temperatures of 2 to 55°C (35 to 131°F). This option is only available for the lower kW rating of fixed speed compressor packages.