

Nirvana Cycling REFRIGERATED AIR DRYERS 200 to 8000 SCFM

Point of Manufacture – West Chester, PA, USA

Industrial Technologies
Davidson, NC 28036

Date: May 1, 2010
Cancels: All Previous

OPTIONAL EQUIPMENT

Electrical Rating

The fans, fan guards and cabinet form a NEMA 1 / IP 21 rated enclosure. NEMA 4 rated enclosure is available as an option.

Large Capacity (8000 SCFM)

For capacity requirements over 8000 SCFM, please contact factory for specification.

Condenser (200-2400 SCFM)

A standard air-cooled condenser for the 200-2400 SCFM dryer is provided as standard. Water-cooled condenser is also an available option on these models.

Condenser (3250-8000 SCFM)

A standard water-cooled condenser for the 3250-8000 SCFM dryer is provided as standard. Air-cooled condenser is an available option.

Drain (200-2400 SCFM)

Timed solenoid drain is provided as standard on the 200 – 2400 SCFM dryers. No air loss drain is an available option on these models.

Voltage Options

(see chart below)

Base Model	Voltage Options					
	230-1-60	230-3-60	220-3-50			
NVC200						
NVC300						
NVC400						
NVC500						
NVC600						
NVC700						
NVC800						
NVC1000						
NVC1200				460-3-60	575-3-60	380-3-50
NVC1600						
NVC2000						
NVC2400						
NVC3250						
NVC4000						
NVC4800						
NVC6000						
NVC8000						